FLIGHT SUMMARY REPORT

Flight Number: 98-044

Calendar/Julian Date: 29 April 1998 • 119

Sensor Package: Wild Heerbrugg RC-10

Airborne Visible and Infrared Imaging

Aircraft #:

809

Spectrometer (AVIRIS)

Area(s) Covered: Rogers Lake, Sierra Nevadas, Jasper

Ridge, Santa Barbara, CA

Investigator(s): Green, JPL; Ustin, UC Davis;

Dozier and Roberts, UCSB

SENSOR DATA

Accession #: 05250 -----

Sensor ID #: 034 099

Sensor Type: RC-10 AVIRIS

Focal Length: 12" -----

304.66 mm

Film Type: Aerochrome IR -----

SO-134

Filtration: Wratten 12 -----

Spectral Band: 510-900 nm -----

f Stop: 11 -----

Shutter Speed: 1/275 -----

of Frames: 132 -----

% Overlap: 60 -----

Quality: Good -----

Remarks:

Airborne Science and Applications Program

The Airborne Science Branch at NASA's Dryden Flight Research Center, Edwards, California, operates two ER-2 high altitude aircraft in support of NASA earth science research. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and in situ data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, Fiji, New Zealand, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

Airborne Visible and Infrared Imaging Spectrometer

The Airborne Visible and Infrared Imaging Spectrometer (AVIRIS) is the second in the series of imaging spectrometer instruments developed at the Jet Propulsion Laboratory (JPL) for earth remote sensing. This instrument uses scanning optics and four spectrometers to image a 614 pixel swath simultaneously in 224 contiguous spectral bands (0.4-2.4 mm).

AVIRIS parameters are as follows:

IFOV: 1 mrad

Ground Resolution: 66 feet (20 meters) at 65,000 feet

Total Scan Angle: 30°

Swath Width: 5.7 nmi (10.6 km) at 65,000 feet

Spectral Coverage: 0.41-2.45 mm

Pixels/Scan Line: 614
Number of Spectral Bands: 224
Digitization: 10-bits
Data Rate: 17 MBPS

	Wavelength	Number of	Sampling	
Spectrometer	Range	Bands	Interval	
1	0.41 - 0.70 mm	31	9.4 nm	
2	0.68 - 1.27 mm	63	9.4 nm	
3	1.25 - 1.86 mm	63	9.7 nm	
4	1.84 - 2.45 mm	63	9.7 nm	

All AVIRIS data is decommutated and archived at JPL and not currently available for public distribution. For further information contact Rob Green at Jet Propulsion Laboratory, 4800 Oak Grove Drive, Mail Stop 183-501, Pasadena, California 91109-8099.

Camera Systems

Various camera systems and films are used for photographic data collection. Film types include high definition color infrared, natural color, and black and white emulsions. Available photographic systems are as follows:

- Wild-Heerbrugg RC-10 metric mapping camera
 - 9 x 9 inch film format
 - 6 inch focal length lens provides area coverage of 16 x 16 nautical miles from 65,000 feet
 - 12 inch focal length lens provides area coverage of 8 x 8 nautical miles from 65,000 feet
- Hycon HR-732 large scale mapping camera
 - 9 x 18 inch film format
 - 24 inch focal length lens provides area coverage of 4 x 8 nautical miles from 65,000 feet
- IRIS II Panoramic camera
 - 4.5 x 34.7 inch film format
 - 24 inch focal length lens
 - 90 degree field of view provides area coverage of 2 x 21.4 nautical miles from 65,000 feet

Data Availability

The U.S. Geological Survey's EROS Data Center at Sioux Falls, South Dakota serves as the archive and product distribution facility for Airborne Science Program aircraft acquired photographic and digital imagery. The photographic archive consists of photography acquired by the program from 1971 to April 1996. For information regarding photography and digital data (including areas of coverage, products, and product costs) contact EROS Data Center, Customer Services, Sioux Falls, South Dakota 57198 (Telephone: 605-594-6151).

As of April 1996 the EROS Data Center no longer receives an archive copy of newly acquired Airborne Science Program photography. Original photography is archived with the Airborne Sensor Facility at Ames Research Center. A user copy of the photography is provided to the principal investigators for each flight. Principal investigators are cited on the first page of their respective flight summary reports. For information regarding photography acquired from April 1996 to the present contact the Airborne Sensor Facility as follows:

Flight Documentation and Data Archive Searches

The following is the web site for flight documentation as published by the Airborne Sensor Facility at NASA Ames Research Center:

http://asapdata.arc.nasa.gov/er-2fsr.html

Additional information regarding flight documentation to include data archive searches, data availability, sensor parameters, and areas of coverage may be obtained from the following:

Airborne Sensor Facility MS 240-6 NASA Ames Research Center Moffett Field, CA 94035-1000 Telephone: (650)604-6252 (FAX 4987)

CAMERA FLIGHT LINE DATA FLIGHT NO. 98-044

Accession # 05250

Sensor # 034

Check	Frame	Time (GMT-hr, min, sec)		Altitude, MSL	
Points	Numbers	START	END	feet/meters	Cloud Cover/Remarks
A - B	6183-6187	18:37:18	18:48:08	65000/19812	Clear
C - D	6188-6203	19:08:16	19:14:28	69000/21030	Clear
E - F	6204-6214	19:22:08	19:26:26	"	Minor cumulus (frames 6204-6206 and 6211-6212)
G - H	6215-6226	19:46:35	19:51:07	u	Minor cumulus (frames 6215-6216)
I - J	6227-6243	19:57:48	20:04:53	70000/21336	Clear
K - L	6244-6254	20:30:06	20:34:21	ш	10% strato-cumulus (frames 6252-6254)
M - N	6255-6264	20:40:28	20:44:33	u	20-90% strato-cumulus (frames 6260-6264)
O - P	6265-6286	21:11:53	21:21:16	u	10-80% strato-cumulus (frames 6265-6268)
Q	6287-6293	21:26:52	21:29:15	n .	10% strato-cumulus (frames 6290-6291); oblique (frames 6290-6293)
Q - R	6294-6314	21:36:08	21:45:20	п	10-30% strato-cumulus (frames 6312-6314)









